

### SUGGESTED SPECIFICATIONS

#### Curlex Single Net (Curlex I)

A specific cut of Great Lakes Aspen curled wood excelsior with 80% six-inch fibers or greater fiber length. It shall be of consistent thickness, with fibers evenly distributed throughout the entire area of the blanket. The top of each blanket shall be covered with photodegradable or biodegradable netting. Material shall not contain any weed seed or chemical additives.

##### Specifications

Recommended Use: Slopes to 2:1, Channel to 7 ft/s, shear stress to 1.75 lb/ft<sup>2</sup>  
 Roll Sizes: 4' x 101.25' (45 yd<sup>2</sup>), 8' x 101.25' (90 yd<sup>2</sup>), 12' x 101.25' (135 yd<sup>2</sup>),  
 16' x 101.25' (180 yd<sup>2</sup>)  
 Standard Weight\*: .73 lb/yd<sup>2</sup>  
 Netting Options: Green, QuickMow White (90 day), FibreNet  
 Color: Natural Aspen or QuickGRASS Green




#### Curlex Double Net (Curlex II)

A specific cut of Great Lakes Aspen curled wood excelsior with 80% six-inch fibers or greater fiber length. It shall be of consistent thickness, with fibers evenly distributed throughout the entire area of the blanket. The top and bottom of each blanket shall be covered with photodegradable or biodegradable netting. Material shall not contain any weed seed or chemical additives.

##### Specifications

Recommended Use: Slopes to 1.5:1, Channels to 9 ft/s, shear stress to 2.25 lb/ft<sup>2</sup>  
 Roll Sizes: 4' x 101.25' (45 yd<sup>2</sup>), 8' x 101.25' (90 yd<sup>2</sup>), 12' x 101.25' (135 yd<sup>2</sup>),  
 16' x 101.25' (180 yd<sup>2</sup>)  
 Standard Weight\*: .73 lb/yd<sup>2</sup>  
 Netting Options: Green, QuickMow White (90 day), FibreNet  
 Color: Natural Aspen or QuickGRASS Green



\*Weight is based on a dry fiber weight basis at time of manufacture. Baseline moisture content of Great Lakes Aspen Excelsior is 22%.

#### Installation

Before installing Curlex blankets, the seedbed shall be inspected by the Owner's Representative to ensure it has been properly compacted and fine graded to remove any existing rills. It shall be free of obstructions, such as tree roots, projections such as stones, and other foreign objects. Grass seed shall match soil conditions to allow for maximum germination, dense vegetation, and a structural root system. Contractor shall proceed when satisfactory conditions are present. After the area has been properly shaped, seeded, fertilized, and compacted, locate the start of the roll, making sure the roll is facing toward the area to be covered, and then roll out the blanket. Blankets shall be rolled out flat, even, and smooth without stretching the material then anchored to the subgrade.

**Slopes:** It is recommended that the blankets be installed in the same direction as the water flow; however, on short slopes it may be more practical to install horizontally across the width of the application. If more than one width is required, simply abut the edges together and secure the blankets with a common row of biodegradable staples, steel staples, or stakes. Overlapping of Curlex excelsior blankets is not required or recommended. An exception is waterway slopes.

**Channels:** Curlex blankets shall be centered to offset a seam in the middle of the waterway. They shall be installed in the same direction as the water flow. The adjoining blankets shall be installed away from the center of channel and concentrated water flow. They shall be secured by a common row of staples. It is usually not necessary to overlap Curlex blankets; however, a 2" shingle type installation shall be used in waterway slopes applications. Curlex blanket installation should continue up the side slopes 3' above the anticipated high water elevation. Flanks exposed to runoff, or sheet flow, must be protected by a check slot or trenched. Curlex blankets shall be trenched at the start of the channel and anchored using a staggered staple pattern at end of roll overlaps and end of roll terminations.

Disclaimer: Curlex is a system for erosion control and re-vegetation on slopes and channels. American Excelsior Company (AEC) believes that the information contained herein to be reliable and accurate for use in erosion control and re-vegetation applications. However, since physical conditions vary from job site to job site and even within a given job site, AEC makes no performance guarantees and assumes no obligation or liability for the reliability or accuracy of information contained herein for the results, safety, or suitability of using Curlex, or for damages occurring in connection with the installation of any erosion control product whether or not made by AEC or its affiliates, except as separately and specifically made in writing by AEC. These specifications are subject to change without notice.

If you would like to receive more information or consult with one of our Customer Care Center Specialists, please call us toll free at (888-352-9582)

PDF download specifications available in the Technical Support Library at [www.curlex.com](http://www.curlex.com)