



GUARANTEED ANALYSIS

(Before Pelletizing)

GYPSUM PRO-SELECT PRILL

for fairways, roughs, residential and commercial turf

Pro Pelleted Gypsum Guaranteed Minimum Chemical Analysis		GUARANTEED MINIMUM PHYSICAL ANALYSIS (Before Pelletizing)	
Calcium Sulfate (CaSO ₄ – 2H ₂ O).....	70%	Screen Size	% Passing
Calicum (Ca) Equivalent.....	24%	8 mesh	100%
Minimum Sulfur (S).....	14%	10 mesh	100%
Noninherent moisture (not more than).....	1%	20 mesh	95%
		40 mesh	90%
Derived from: Gypsum, CaSO ₄ – 2H ₂ O		50 mesh	85%
CAS# 14798-04-0	F-1358	60 mesh	75%
		100 mesh	54%

**** Finished pellets through 4 x 14 screens – SGN 250 ****

SUGGESTED SPREADER SETTING (Pounds per 1000 Square Feet)			
	10#	20#	40#
CENTRAL 50	6-1/2	8	10
CYCLONE	5	7	9*
EV-N-SPREAD.....	14-1/2	20	34
FRANKS	3	7-1/2	16-1/2
LESCO	J	N	S
SCOTTS SG 1	6	8-1/2	16
SCOTTS PPE/PF4 (DROP)	6-1/2	9	16
SEARS	3-1/2	4-1/2	6-1/2
SEARS (DROP).....	5-1/2	7	10
SPYKER	4-1/2	5-1/2	8-1/2

*Requires 2 passes for recommended coverage.
These settings are estimated. Actual settings depend on type, model & condition of spreader



550 South Biesecker Road
Thomasville, PA 17364
800-526-1753 or 570-236-7062