



GUARANTEED ANALYSIS

Thomasville, PA
(Before Pelletizing)

CALCITIC LIMESTONE MICRO-SELECT PRILL

for immediate play on greens, tees, grass courts, and fine turf

Pro Pelleted Calcitic Limestone Minimum Guaranteed Chemical Analysis

Calcium (Ca).....	34.83%
Magnesium (Mg).....	2.45%
Calcium Oxide (CaO).....	48.75%
Magnesium Oxide (MgO).....	4.06%
Calcium Carbonate (CaCO ₃).....	87.00%
Magnesium Carbonate (MgCO ₃).....	8.50%
Maximum Moisture Content.....	1.00%
Calcium Carbonate Equivalent - CCE.....	97%
Effective Neutralizing Power - ENP.....	1,809 lbs. per ton
Effective Neutralizing Value - ENV.....	88%
Total Neutralizing Power - TNP.....	97%
Relative Neutralizing Value - RNV.....	95%
Effective Calcium Carbonate Equivalent - ECCE.....	90%
Fineness Factor.....	93%
Index Zone.....	80-89

Derived from Calcitic Limestone
CAS# 1317-65-3

F1358

Guaranteed Minimum Screen Analysis (Before Pelletizing)

Screen Size	% Passing
8 mesh.....	100%
10 mesh.....	100%
20 mesh.....	100%
40 mesh.....	94%
50 mesh.....	93%
60 mesh.....	85%
100 mesh.....	82%

Agricultural Liming Materials

Classification..... Fine Pulverized
Grade A liming Material

**** Finished pellets through 14 x 22 screens – SGN 100 ****

SUGGESTED SPREADER SETTING (Pounds per 1000 Square Feet)

	10#	20#	40#
CENTRAL 50.....	6-1/2	8	10
CYCLONE.....	5	7	9*
EV-N-SPREAD.....	14-1/2	20	34
FRANKS.....	3	7-1/2	16-1/2
LESCO.....	J	N	S
SCOTTS SG 1.....	6	8-1/2	16
SCOTTS PPE/PF4 (DROP).....	6-1/2	9	16
SEARS.....	3-1/2	4-1/2	6-1/2
SEARS (DROP).....	5-1/2	7	10
SPYKER.....	4-1/2	5-1/2	8-1/2

*Requires 2 passes for recommended coverage.

These settings are estimated. Actual settings depend on type, model & condition of spreader



550 South Biesecker Road
Thomasville, PA 17364
800-526-1753 or 570-236-7062