



GUARANTEED ANALYSIS

Thomasville, PA
(Before Pelletizing)

DOLOMITIC LIMESTONE MICRO-SELECT PRILL

for immediate play on greens, tees, grass courts, and fine turf

Guaranteed Minimum Chemical Analysis

Calcium (Ca)	20.80%
Magnesium (Mg)	11.70%
Calcium Oxide (CaO)	29.10%
Magnesium Oxide (MgO)	19.40%
Calcium Carbonate (CaCO ₃)	52.00%
Magnesium Carbonate (MgCO ₃)	40.50%
Maximum Moisture Content	1.00%
Calcium Carbonate Equivalent - CCE	100%
Effective Neutralizing Power - ENP	1,888 lbs. per ton
Effective Neutralizing Value - ENV	91%
Total Neutralizing Power - TNP	100%
Relative Neutralizing Value - RNV	98%
Effective Calcium Carbonate Equivalent - ECCE	94%
Fineness Factor	94%
Index Zone	70-79
Derived from Dolomitic limestone	
CAS# 16389-88-1	F1358

Guaranteed Minimum Screen Analysis (Before Pelletizing)

Screen Size	% Passing
8 mesh	100%
10 mesh	100%
20 mesh	100%
40 mesh	95%
50 mesh	90%
60 mesh	88%
100 mesh	80%

Agricultural Liming Materials

Classification..... Fine Pulverized
Grade A liming Material

**** Finished pellets through 14 x 22 screens – SGN 100 ****

SUGGESTED SPREADER SETTING (Pounds per 1000 Square Feet)

	10#	20#	40#
CENTRAL 50	6-1/2	8	10
CYCLONE	5	7	9*
EV-N-SPREAD	14-1/2	20	34
FRANKS	3	7-1/2	16-1/2
LESCO	J	N	S
SCOTTS SG 1	6	8-1/2	16
SCOTTS PPE/PF4 (DROP)	6-1/2	9	16
SEARS	3-1/2	4-1/2	6-1/2
SEARS (DROP)	5-1/2	7	10
SPYKER	4-1/2	5-1/2	8-1/2

*Requires 2 passes for recommended coverage.

These settings are estimated. Actual settings depend on type, model & condition of spreader



550 South Biesecker Road
Thomasville, PA 17364
800-526-1753 or 570-236-7062