

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	GREENYARD PROFESSIONAL FERTILIZER 13-0-5 25%XCU .37% CAVALCADE
----------------------	--

SECTION I	
MANUFACTURER'S NAME: GROWMARK, FS LLC 3150 Stoney Point Rd East Berlin PA 17316 (717)259-9573	EMERGENCY TELEPHONE NUMBER CALL DAY OR NIGHT 1-800-424-9300 TELEPHONE NUMBER FOR INFORMATION: (888)222-4405

SECTION II CHEMICAL INGREDIENTS / IDENTITY INFORMATION

<u>CHEMICAL COMPONENTS</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OTHER LIMITS</u>	<u>CAS #</u>	<u>%</u>
Urea	5mg/M ³	10mg/M ³		57-13-6	
Limestone					
Polymer Coated Sulfur Coated Urea (XCU)		10mg/M3		57-13-6	
Clay	5mg/M3	10mg/M3		1302-78-9	
Potassium Chloride		10mg/M3		7447-40-7	
Prodiamine				29091-21-2	.37

SECTION III PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT	NA	SPECIFIC GRAVITY	>1
VAPOR PRESSURE	NA	MELTING POINT	132.7 ⁰ C
VAPOR DENSITY	NA	EVAPORATION RATE	NA
SOLUBILITY IN WATER	Soluble	APPEARANCE AND ODOR	Granular & mixed color

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): NA

EXTINGUISHING MEDIA: FOAM & WATER

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and self-contained breathing apparatus, to protect against the decomposition products of Urea and Sulfur Coated Urea which can be toxic.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Avoid breathing vapors or dust.

SECTION V REACTIVITY DATA

STABLE	X	CONDITIONS TO AVOID	Decomposes when heated above melting point
UNSTABLE		CONDITIONS TO AVOID	

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid Contact with Strong Acids, Mildly Corrosive to Metals in Presence of Moisture

HAZARDOUS DECOMPOSITION OR BY PRODUCTS: NDA

<u>HAZARDOUS POLYMERIZATION:</u>			
MAY OCCUR		CONDITIONS TO AVOID	
WILL NOT OCCUR	X	CONDITIONS TO AVOID	N A

SECTION VI HEALTH HAZARD DATA

ROUTES OF ENTRY: Inhalation, Eyes, Skin, and Ingestion

HEALTH HAZARDS:

SIGNS AND SYMPTOMS OF EXPOSURE: EYES: Dust and vapors can cause irritation and pain. SKIN: Can cause irritation. INHALATION: Dust can cause sore throat, coughing, and shortness of breath. INGESTION: Can cause sore throat and abdominal pain.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NDA

EMERGENCY AND FIRST AID PROCEDURES: EYES & INGESTION: Flush immediately with plenty of water, seek medical attention if necessary. SKIN: Remove contaminated clothing immediately and flush contaminated area with water. INHALATION: Move to fresh air and rest. Seek medical attention if necessary.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Sweep up and reuse as product.

WASTE DISPOSAL METHOD: Sanitary Landfill. Dispose in compliance with local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in dry location, remote from acids.

OTHER PRECAUTIONS:

SECTION VIII CONTROL MEASURES / PROCESS AREAS

RESPIRATORY PROTECTION (SPECIFY TYPE):

VENTILATION	LOCAL EXHAUST	as necessary to maintain low dust levels
	MECHANICAL	N A
	SPECIAL	dust mask or respirator in dusty situations

PROTECTIVE GLOVES: Gloves recommended EYE PROTECTION: None required

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Optional

WORK / HYGIENIC PRACTICES: Normally accepted practices.

SECTION IX REGULATORY COMPLIANCE

THE FOLLOWING INFORMATION MAY BE USEFUL IN COMPLYING WITH VARIOUS STATE AND FEDERAL LAWS AND REGULATIONS UNDER VARIOUS ENVIRONMENTAL STATUTES:

REPORTABLE QUANTITY (RQ), EPA REGULATION 40 CFR 302 (CERLA Section 102):

CHEMICAL NAMES	CAS#	RQ
		NA

THRESHOLD PLANNING QUANTITY (TPQ), EPA REGULATION 40 CFR 355 (SARA Sections 301-304):

CHEMICAL NAME:	CAS#:	TPQ:
----------------	-------	------

TOXIC CHEMICAL RELEASE REPORTING, EPA REGULATION 40 CFR 372 (SARA Section 313):

CHEMICAL NAME:	CAS #:	% BY WEIGHT IN PRODUCT
----------------	--------	------------------------

HAZARDOUS CHEMICAL REPORTING, EPA REGULATION 40 CFR 370 (SARA Sections 311-312):

CHEMICAL NAME:	CAS#:
----------------	-------

EPA HAZARD CLASSIFICATION CODE:

ACUTE HAZARD	CHRONIC HAZARD	FIRE HAZARD	PRESSURE HAZARD	REACTIVE HAZARD	NOT APPLICABLE
					X

HAZARD RATING: NFPA

__0__ FIRE	__0__ TOXICITY	__0__ REACTIVITY	__U__ CORROSIVENESS
------------	----------------	------------------	---------------------

HAZARD RATING CODE	0 None	1 Slight	2 Moderate	3 High	U Unknown
--------------------	--------	----------	------------	--------	-----------

SECTION X TRANSPORTATION INFORMATION

For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Material Incidents. DOT P 5800.5

DOT IDENTIFICATION:

RQ:

OSHA REQUIRED LABEL INFORMATION:

In compliance with hazard and right-to-know requirements, the following OSHA Hazard Warnings should be found on a label, bill of lading or invoice accompanying this shipment. NA

NOTE: Product label will contain additional non-OSHA related information.

DATE: January 3, 2013

SUPERSEDES: ALL PREVIOUS

The information herein was given in good faith but no warranty, expressed or implied was made. Consult for further information.

NA = NOT APPLICABLE

NDA = NO DATA AVAILABLE